



SCALE 1:5



SCALE 1: 10

① SUPPORT BEAM FIXING TO EXIST. FLOOR BEAM
USE MULTIGRIP TO ONE SIDE, ALL HOLES FILLED.
NOTE: ONE SIDE TYPICALLY BLOCKED BY EXISTING STRUCTURE
(USE PAIR WHERE PRACTICAL)

- ② FIXING OVER SUPPORT
USE DIAGONAL NAIL CLEAT N21 HORIZONTAL ONE SIDE,
ALL HOLES FILLED BETWEEN SIDE OF CANTILEVER BEAM
AND TOP OF SUPPORT BEAM/ TOP PLATE.
- WHERE NO 'STUD' AT 'LOCATION OF' CANTILEVER, 'USE
140x45 SGB PACKER BETWEEN STUDS -FIX EACH END
WITH 4 NAILS MIN. (MUST BE TIGHT FIT AGAINST
CANTILEVER BEAM NOTCH.)

NU-WALL CLADDING ON
CAVITY BATTENS OVER —
RAB BOARD TO FRAMING
MITRE RETURN FASCIA BD.
RAKING UNDER PLY DECK
SEAL TO CLADDING



SCALE 1:5

11 HARGREAVES STREET • PONSONBY • AUCKLAND • TEL 379-3718 • FAX 379-3711
E-MAIL: INFO@SHANAHANARCHITECTS.CO.NZ

EDEN 1
MT EDEN, AUCKLAND

C	CONSTRUCTION	D45
	8 11 13	

SECTION